



## Material Safety Data Sheet

Copyright, 2013, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** 3M™ HEAVY DUTY MULTI-SURFACE CLEANER Concentrate (Twist 'n Fill™ Product No. 2)  
**MANUFACTURER:** 3M  
**DIVISION:** Building & Commercial Services Division  
**ADDRESS:** 3M Center, St. Paul, MN 55144-1000

**EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)**

**Issue Date:** 01/31/13  
**Supersedes Date:** 11/30/12

**Document Group:** 30-9232-7

#### Product Use:

**Specific Use:** Versatile cleaner removes most spots, stains and grease from washable surfaces. Use to clean carpets, marble, aluminum, stainless steel, chrome, etc.  
**Intended Use:** Hard Surface Cleaner

### SECTION 2: INGREDIENTS

| <u><b>Ingredient</b></u>                     | <u><b>C.A.S. No.</b></u> | <u><b>% by Wt</b></u> |
|----------------------------------------------|--------------------------|-----------------------|
| WATER                                        | 7732-18-5                | 60 - 90               |
| Non-ionic Surfactants (NJTSRN 04499600-6659) | Trade Secret             | 10 - 30               |
| 2-AMINOISOBUTANOL                            | 124-68-5                 | 1 - 5                 |
| Surfactant (NJTSRN 004499600-6632)           | Trade Secret             | 0.5 - 1.5             |
| SODIUM LAUROYL SARCOSINATE                   | 137-16-6                 | 0.1 - 1               |

### SECTION 3: HAZARDS IDENTIFICATION

#### 3.1 EMERGENCY OVERVIEW

**Specific Physical Form:** Liquid

**Odor, Color, Grade:** Purple color citrus fragrance

**General Physical Form:** Liquid

**Immediate health, physical, and environmental hazards:** Combustible liquid and vapor. Closed containers exposed to heat from

fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back. May cause chemical eye burns. May cause severe skin irritation. May cause allergic skin reaction.

## 3.2 POTENTIAL HEALTH EFFECTS

### **Eye Contact:**

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

### **Skin Contact:**

Severe Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

### **Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

## 3.3 POTENTIAL ENVIRONMENTAL EFFECTS

A 3M Product Environmental Data Sheet (PED) is available.

## SECTION 4: FIRST AID MEASURES

### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention.

**Skin Contact:** Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

**Inhalation:** Remove person to fresh air. If signs/symptoms develop, get medical attention.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

## SECTION 5: FIRE FIGHTING MEASURES

### 5.1 FLAMMABLE PROPERTIES

**Flash Point**  
**Flammable Limits(LEL)**  
**Flammable Limits(UEL)**

185 °F [Test Method: Tagliabue Closed Cup]  
Not Applicable  
Not Applicable

OSHA Flammability Classification:

Class IIIA Combustible Liquid

## 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

## 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** Combustible liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

**Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.**

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode.

### 6.2. Environmental precautions

Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

### Clean-up methods

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with water.

**In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.**

## SECTION 7: HANDLING AND STORAGE

### 7.1 HANDLING

Keep out of the reach of children. This product is not intended to be used without prior dilution as specified on the product label. Avoid breathing of vapors, mists or spray. Avoid skin contact. Do not get in eyes. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Avoid contact with oxidizing agents.

### 7.2 STORAGE

Store away from heat. Store out of direct sunlight. Store away from acids. Store away from oxidizing agents.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 ENGINEERING CONTROLS

Use in a well-ventilated area. NOTE: When used as directed and diluted and dispensed with a TWIST 'n FILL(TM) Chemical Dispenser, special ventilation is not required.

## 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

### 8.2.1 Eye/Face Protection

Do not get in eyes. NOTE: When used as directed and diluted and dispensed with a TWIST 'n FILL(TM) Chemical Dispenser, eye contact with the concentrate is not expected to occur.

If the product is not used with the Twist 'n Fill system or if there is an accidental release, the following eye protection is recommended: Full Face Shield, Indirect Vented Goggles.

### 8.2.2 Skin Protection

Avoid skin contact. NOTE: When used as directed and diluted and dispensed with a TWIST 'n FILL(TM) Chemical Dispenser, skin contact with the concentrate is not expected to occur.

If the product is not used with the Twist 'n Fill system or if there is an accidental release, select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials. Gloves made from the following material(s) are recommended: Butyl Rubber, Neoprene, Nitrile Rubber. The following protective clothing material(s) are recommended: Apron - Neoprene.

### 8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray. NOTE: When used as directed and diluted and dispensed with a TWIST 'n FILL(TM) Chemical Dispenser, respiratory protection is not required.

If the product is not used with the Twist 'n Fill system or if there is an accidental release, select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

### 8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

## 8.3 EXPOSURE GUIDELINES

None Established

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

|                         |                                                             |
|-------------------------|-------------------------------------------------------------|
| Specific Physical Form: | Liquid                                                      |
| Odor, Color, Grade:     | Purple color citrus fragrance                               |
| General Physical Form:  | Liquid                                                      |
| Flash Point             | 185 °F [Test Method: Tagliabue Closed Cup]                  |
| Flammable Limits(LEL)   | Not Applicable                                              |
| Flammable Limits(UEL)   | Not Applicable                                              |
| Boiling Point           | 212 °F [Test Method: Estimated]                             |
| Vapor Pressure          | < 33 mmHg [@ 131 °F]                                        |
| Specific Gravity        | Approximately 1 [Test Method: Estimated] [Ref Std: WATER=1] |

|                                |                                                          |
|--------------------------------|----------------------------------------------------------|
| pH                             | 10.5 - 11.6                                              |
| Solubility in Water            | Complete                                                 |
| Volatile Organic Compounds     | 5 - 6 % [Test Method: calculated per CARB title 2]       |
| VOC Less H2O & Exempt Solvents | 350 - 395 g/l [Test Method: calculated per CARB title 2] |
| Viscosity                      | 5 centipoise                                             |

## SECTION 10: STABILITY AND REACTIVITY

**Stability:** Stable.

### Materials and Conditions to Avoid:

#### 10.1 Conditions to avoid

Not determined

#### 10.2 Materials to avoid

Strong oxidizing agents

Strong acids

**Hazardous Polymerization:** Hazardous polymerization will not occur.

### Hazardous Decomposition or By-Products

| <u>Substance</u>   | <u>Condition</u> |
|--------------------|------------------|
| Carbon monoxide    | Not Specified    |
| Carbon dioxide     | Not Specified    |
| Oxides of Nitrogen | Not Specified    |

## SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

## SECTION 12: ECOLOGICAL INFORMATION

### ECOTOXICOLOGICAL INFORMATION

Not determined.

### CHEMICAL FATE INFORMATION

Not determined.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Dispose of waste product in a facility permitted to accept chemical waste. As a disposal alternative, incinerate in an industrial or commercial facility.

**EPA Hazardous Waste Number (RCRA):** Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

## SECTION 14: TRANSPORT INFORMATION

### ID Number(s):

70-0715-9457-9, 70-0715-9458-7

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: REGULATORY INFORMATION

### US FEDERAL REGULATIONS

#### 311/312 Hazard Categories:

Fire Hazard - Yes   Pressure Hazard - No   Reactivity Hazard - No   Immediate Hazard - Yes   Delayed Hazard - No

### STATE REGULATIONS

### CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS. The components of this product are listed on the Canadian Domestic Substances List.

### INTERNATIONAL REGULATIONS

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: OTHER INFORMATION

### NFPA Hazard Classification

Health: 3   Flammability: 2   Reactivity: 0   Special Hazards: None

Acid/Base: Alkaline

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### HMIS Hazard Classification

Health: 3   Flammability: 2   Reactivity: 0   Protection: X - See PPE section.

Hazardous Material Identification System (HMIS®) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint and Coatings Association (NPCA).

Revision Changes:

Section 1: Product name was modified.

Copyright was modified.

Section 16: Web address was added.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

**3M USA MSDSs are available at [www.3M.com](http://www.3M.com)**