Section 1: Product & Company Identification

Product Name: Lectra Clean® Heavy Duty Electrical Parts Degreaser (aerosol)

Product Number (s): 02018, 02018-6, 72018

Product Use: Energized Electrical Cleaner

Manufacturer / Supplier Contact Information:

<u>In United States</u>: <u>In Canada</u>: <u>In Mexico</u>:

CRC Industries, Inc.

CRC Canada Co.

CRC Industries Mexico

2-1246 Lorimar Drive

Av. Benito Juárez 4055 G

Warminster, PA 18974 Mississauga, Ontario L5S 1R2 Colonia Orquídea

<u>www.crcindustries.com</u> <u>www.crc-canada.ca</u> San Luís Potosí, SLP CP 78394

1-215-674-4300 (General) 1-905-670-2291 <u>www.crc-mexico.com</u> (800) 521-3168 (Technical) 52-444-824-1666 (800) 272-4620 (Customer Service)

24-Hr Emergency – CHEMTREC: (800) 424-9300 or (703) 527-3887

Section 2: Hazards Identification

Emergency Overview

DANGER: Vapor Harmful. Contents Under Pressure. Appearance & Odor: Colorless liquid, irritating odor at high concentrations

Potential Health Effects:

ACUTE EFFECTS:

EYE: May cause slight temporary eye irritation. Vapors may irritate the eyes at concentrations of 100 ppm.

SKIN: Short single exposures may cause skin irritation. Prolonged exposure may cause severe skin irritation,

even a burn. A single prolonged exposure is not likely to result in the material being absorbed through

skin in harmful amounts.

INHALATION: Dizziness may occur at concentrations of 200 ppm. Progressively higher levels may also cause nasal

irritation, nausea, incoordination, and drunkenness. Very high levels or prolonged exposure could lead

to unconsciousness and death.

INGESTION: Single dose oral toxicity is considered to be extremely low. Swallowing large amounts may cause

injury if aspirated into the lungs. This may be rapidly absorbed through the lungs and result in injury to

other body systems.

CHRONIC EFFECTS: Repeated contact with skin may cause drying or flaking of skin. Excessive or long term

exposure to vapors may increase sensitivity to epinephrine and increase myocardial irritability.

TARGET ORGANS: Central nervous system. Possibly liver and kidney.

Medical Conditions Aggravated by Exposure: None known.

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Product Number (s): 02018, 02018-6, 72018

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.	
Tetrachloroethylene (PERC)	127-18-4	> 95	
Carbon Dioxide	124-38-9	< 5	
Decafluoropentane (HFC-43-10mee)	138495-42-8	< 2	

Section 4: First Aid Measures

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician if

irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If

breathing is difficult give oxygen. Call a physician.

Ingestion: Do NOT induce vomiting. Call a physician immediately.

Note to Physicians: Because rapid absorption may occur through lungs if aspirated and cause systemic effects, the

decision of whether to induce vomiting or not should be made by a physician. If lavage is performed, suggest endotracheal and/or esophageal control. If burn is present, treat as any thermal burn, after decontamination. Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary. No specific antidote.

Section 5: Fire-Fighting Measures

Flammable Properties: This product is nonflammable in accordance with aerosol flammability definitions.

(See 16 CFR 1500.3(c)(6))

Flash Point: None (TCC) Upper Explosive Limit: None Autoignition Temperature: None Lower Explosive Limit: None

Fire and Explosion Data:

Suitable Extinguishing Media: This material does not burn. Use extinguishing agent suitable for surrounding fire.

Products of Combustion: Hydrogen chloride, trace amounts of phosgene and chlorine

Explosion Hazards: Aerosol containers, when exposed to heat from fire, may build pressure and explode.

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for

protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool

and to knock down vapors which may result from product decomposition.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8. Do not breathe vapors.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into

sewers or storm drains.

Methods for Containment & Clean-up: Dike area to contain spill. Ventilate the area with fresh air. If in confined space

Product Number (s): 02018, 02018-6, 72018

or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Vapors of this product are heavier than air and will collect in low areas. Make sure ventilation

removes vapors from low areas. Do not eat, drink or smoke while using this product. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. For

product use instructions, please see the product label.

Storage Procedures: Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120°F /

49°C to prevent cans from rupturing.

Aerosol Storage Level: I

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

	OSHA		ACGIH		OTHER		
COMPONENT	TWA	STEL	TWA	STEL	TWA	SOURCE	UNIT
Tetrachloroethylene	100	N.E.	25	100	N.E.		ppm
Decafluoropentane	N.E.	N.E.	N.E.	N.E.	200	mfr	ppm
Carbon dioxide	5000	30000 v	5000	30,000	N.E.		ppm
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

Controls and Protection:

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally

preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA

regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls

are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and

for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid

contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as PVA, Teflon, or Viton. Also, use full protective clothing if there is

prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: liquid Color: colorless Odor: irritating odor

Product Number (s): 02018, 02018-6, 72018

Odor Threshold: 50 ppm Specific Gravity: 1.619

Initial Boiling Point: 250°F / 121°C

Freezing Point: ND

Vapor Pressure: 13 mmHg @ 68°F / 20°C Vapor Density: 5.76 (air = 1)

Evaporation Rate: very fast

Solubility: 0.015 g/ 100 g @ 77°F / 25°C in water

Coefficient of water/oil distribution (log P_{ow}): 2.88

pH: NA

Volatile Organic Compounds (Federal): wt %: 0 g/L: 0 lbs./gal: 0

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Avoid direct sunlight or ultraviolet sources. Avoid open flames, welding arcs, and other high

temperature sources which induce thermal decomposition.

Incompatible Materials: Avoid contact with metals such as: aluminum powders, magnesium powders, potassium,

sodium, and zinc powder. Avoid unintended contact with amines. Avoid contact with strong

bases and strong oxidizers.

Hazardous Decomposition Products: Hydrogen chloride, trace amounts of chlorine and phosgene

Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

Acute Toxicity:

<u>Component</u>	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 (rat)
Tetrachloroethylene	2629 mg/kg	> 10 g/kg	5200 mg/kg/4H
Carbon dioxide	No data	No data	470,000 ppm/30M
Decafluoropentane	> 5000 mg/kg	> 5000 mg/kg	11,100 ppm/4H

Chronic Toxicity:

	OSHA	IARC	NTP		
<u>Component</u>	Carcinogen	Carcinogen	<u>Carcinogen</u>	<u>Irritant</u>	Sensitizer
Tetrachloroethylene	No	Group 2A	Reasonably Anticipated to	E (mild) /	No
		-	be a Carcinogen	S (severe)	
Carbon dioxide	No	No	No	None	No
Decafluoropentane	No	No	No	E (mild)	No

Reproductive Toxicity: No information available Teratogenicity: No information available

<u>Mutagenicity</u>: Tetrachloroethylene: in vitro studies were negative

animal studies were negative

Synergistic Effects: No information available

Product Number (s): 02018, 02018-6, 72018

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: Tetrachloroethylene -- 96 Hr LC50 Rainbow Trout: 5.28 mg/L (static)

96 Hr LC50 Fathead minnow: 13.4 mg/L (flow-through)

Persistence / Degradability: Biodegradation under aerobic conditions is below detectable limits.

Biodegradation may occur under anaerobic conditions. Biodegradation rate may

increase in soil and/or water with acclimation.

Bioaccumulation / Accumulation: Bioconcentration potential is low (BCF less than 100).

Mobility in Environment: Potential for mobility in soil is medium.

Section 13: Disposal Considerations

Waste Classification: The dispensed liquid product is a RCRA hazardous waste for toxicity with the following potential

waste codes: U210, F001, F002, D039. (See 40 CFR Part 261.20 – 261.33)

Aerosol containers should be fully emptied and depressurized before disposal. Empty

containers may be recycled.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

Section 14: Transport Information

US DOT (ground): UN1950, Aerosols, poison, Packing Group III, 2.2 (6.1), Limited Quantity

ICAO/IATA (air): UN1950, Aerosols, nonflammable, containing substances in Division 6.1, Packing Group III,

2.2 (6.1), Limited Quantity

IMO/IMDG (water): UN1950, Aerosols, 2.2 (6.1)

Special Provisions: Marine Pollutant

DOT: Forbidden from transportation by air

Section 15: Regulatory Information

U.S. Federal Regulations:

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: Tetrachloroethylene (100 lbs)

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories: Fire Hazard No

Reactive Hazard No Release of Pressure Yes

Page 5 of 7

Product Number (s): 02018, 02018-6, 72018

Acute Health Hazard Yes Chronic Health Hazard Yes

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986

and 40 CFR Part 372:

Tetrachloroethylene (97.4%)

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): Tetrachloroethylene

Occupational Safety and Health Administration:

This product is regulated by the Hazard Communications Standard.

U.S. State Regulations:

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm:

Tetrachloroethylene

Consumer Products VOC Regulations: For users in California, Connecticut, Delaware, District of Columbia, Illinois, Indiana,

Maine, Maryland, Massachusetts, Michigan, New Jersey, New York, Ohio, Pennsylvania, Rhode Island and Virginia, this product is an Energized Electrical Cleaner. Energized equipment use only. Not to be used for motorized vehicle

maintenance or their parts.

State Right to Know:

New Jersey: 127-18-4, 124-38-9 Pennsylvania: 127-18-4, 124-38-9 Massachusetts: 127-18-4, 124-38-9 Rhode Island: 127-18-4, 124-38-9

Canadian Regulations:

Controlled Products Regulations:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: A, D1B, D2A, D2B

<u>Canadian DSL Inventory</u>: All ingredients are either listed on the DSL Inventory or are exempt.

European Union Regulations:

RoHS Compliance: This product is compliant with Directive 2002/95/EC of the European Parliament and of the Council of

27 January 2003. This product does not contain any of the restricted substances as listed in Article

4(1) of the RoHS Directive.


Additional Regulatory Information: None

Product Number (s): 02018, 02018-6, 72018

Section 16: Other Information

HMIS® (II)		
Health:	2	
Flammability:	0	
Reactivity:	0	
PPE:	В	

Ratings range from 0 (no hazard) to 4 (severe hazard)



Prepared By: Michelle Rudnick

CRC #: 863A Revision Date: 03/27/2014

Changes since last revision: Section 14: Transport Information

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstract Service
CFR: Code of Federal Regulations
DOT: Department of Transportation
DSL: Domestic Substance List

g/L: grams per Liter

HMIS: Hazardous Materials Identification System IARC: International Agency for Research on Cancer

IATA: International Air Transport Association ICAO: International Civil Aviation Organization IMDG: International Maritime Dangerous Goods IMO: International Maritime Organization

lbs./gal: pounds per gallon LC: Lethal Concentration

LD: Lethal Dose

NA: Not Applicable ND: Not Determined

NIOSH: National Institute of Occupational Safety & Health

NFPA: National Fire Protection Association

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PMCC: Pensky-Martens Closed Cup PPE: Personal Protection Equipment

ppm: Parts per Million

RoHS: Restriction of Hazardous Substances

STEL: Short Term Exposure Limit

TCC: Tag Closed Cup
TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Information

System