



Revision Number: 002.0 Issue date: 09/27/2012

1. PRODUCT AND COMPANY IDENTIFICATION

LOCTITE® AVIATION GASKET Product name:

SEALANT

Product type: Sealant

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

IDH number: 497095

Item number: 37559

Region: **United States**

Contact information: Telephone: 860.571.5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

HEALTH: *2 Physical state: **Paste** Color: Dark brown FLAMMABILITY: 3 PHYSICAL HAZARD: Odor: Alcoholic 0

> Personal Protection: See MSDS Section 8

WARNING: FLAMMABLE LIQUID AND VAPOR.

MAY CAUSE ALLERGIC SKIN REACTION.

CAUSES EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

May cause irritation to nose and throat. May cause respiratory tract irritation. Inhalation:

Skin contact: May cause allergic skin reaction. May cause skin irritation. Vapors may irritate eyes. Contact with eyes will cause irritation. Eye contact:

Ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Existing conditions aggravated by

exposure:

Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Castor oil, oxidized	68187-84-8	30 - 60
Rosin	8050-09-7	10 - 30
Methyl acetate	79-20-9	10 - 30
Talc	14807-96-6	10 - 30
Quartz (SiO2)	14808-60-7	0.1 - 1
Methanol	67-56-1	0.1 - 1

IDH number: 497095 Product name: LOCTITE® AVIATION GASKET SEALANT

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. Wash clothing before reuse. If symptoms

develop and persist, get medical attention.

Eye contact: Flush with copious amounts of water, preferably, lukewarm water for at least

15 minutes, holding evelids open all the time. Get medical attention.

Ingestion: Do not induce vomiting. Keep individual calm. Get medical attention.

5. FIRE FIGHTING MEASURES

Flash point: 8 °C (46.4 °F)

Autoignition temperature: Not available.

Flammable/Explosive limits - lower: Not available.

Flammable/Explosive limits - upper: Not available.

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: None

Hazardous combustion products: Oxides of carbon. Acrid smoke and fumes. Carboxylic acids. Aldehydes.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways. Do not allow product to

enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Ensure adequate ventilation. Scrape up spilled

material and place in a closed container for disposal. Remove all sources of ignition. Ensure adequate ventilation. Scrape up spilled material and place in a

closed container for disposal.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling.

Storage: Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

IDH number: 497095 Product name: LOCTITE® AVIATION GASKET SEALANT

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Castor oil, oxidized	None	None	None	None
Rosin	Exposure by all routes should be carefully controlled to levels as low as possible. Included in the regulation but with no data values. See regulation for further details (Sensitiser.)	None	None	None
Methyl acetate	200 ppm TWA 250 ppm STEL	200 ppm (610 mg/m3) TWA	None	None
Talc	2 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 20 MPPCF TWA 0.3 mg/m3 TWA Total dust.	None	50 ppm
Quartz (SiO2)	0.025 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	None
Methanol	200 ppm TWA (SKIN) 250 ppm STEL	200 ppm (260 mg/m3) TWA	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use a NIOSH approved supplied air respirator if the potential to exceed

established exposure limits exists.

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin

contact. Disposable rubber or plastic gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Not available.

Physical state:PasteColor:Dark brownOdor:AlcoholicOdor threshold:Not available.pH:Not available.

 Vapor pressure:
 33 mm hg (20 °C (68°F))

 Boiling point/range:
 82 °C (179.6 °F)

Melting point/ range:
Specific gravity:
1.17
Vapor density:
2.07

IDH number: 497095

Flash point:

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

8 °C (46.4 °F)

Not available.

Not available.

Not available.

Not available.

VOC content: 0.42 %; 4.91 g/l EPA Method 24

10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition products: Aldehydes. Carboxylic acids. Acrid smoke and fumes. Oxides of carbon.

Incompatible materials: Strong oxidizing agents. Acids.

Conditions to avoid: See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Castor oil, oxidized	No	No	No
Rosin	No	No	No
Methyl acetate	No	No	No
Talc	No	No	No
Quartz (SiO2)	Known To Be Human Carcinogen.	Group 1	No
Methanol	No	No	No

Hazardous components	Health Effects/Target Organs
Castor oil, oxidized	No Records
Rosin	Respiratory, Irritant, Allergen
Methyl acetate	Blood, Central nervous system, Eyes, Irritant
Talc	Irritant, Lung, Some evidence of carcinogenicity
Quartz (SiO2)	Immune system, Lung, Some evidence of carcinogenicity
Methanol	Eyes, Heart, Irritant, Kidney, Liver, Metabolic, Nervous System, Reproductive

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: D001: Ignitable.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:Resin solutionHazard class or division:3Identification number:UN 1866Packing group:II

International Air Transportation (ICAO/IATA)

Proper shipping name: Resin solution Hazard class or division: 3 UN 1866

Packing group:

Exceptions: Consumer Commodity, ID 8000, Class 9, (Not more than 500 ml)

IDH number: 497095 Product name: LOCTITE® AVIATION GASKET SEALANT

Water Transportation (IMO/IMDG)

Proper shipping name: RESIN SOLUTION

Hazard class or division: 3 Identification number: UN 1866

Packing group:

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12(b) Export Notification: Blown castor oil (CAS# 68187-84-8).

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA 313:

None above reporting de minimis
Immediate Health, Delayed Health
None above reporting de minimis

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List. WHMIS hazard class: B.2, D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 1, 2, 9

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 497095 Product name: LOCTITE® AVIATION GASKET SEALANT