

MEGUIAR'S G120 - HOT SHINE TIRE DRESSING

Chemwatch Independent Material Safety Data Sheet
Issue Date: 1-Sep-2011
C9317EC

CHEMWATCH 4827-55
Version No:5
CD 2011/2 Page 1 of 6

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

MEGUIAR'S G120 - HOT SHINE TIRE DRESSING

SYNONYMS

"Product Code: G120", "Ref No: 20-101A"

PRODUCT USE

■ Used according to manufacturer's directions.
Automotive. Protective tire coating.

SUPPLIER

Company: MotorActive
Address:
35 Slough Business Park, Holker Street
Silverwater
NSW, 2128
Australia
Telephone: +61 2 9737 9422
Telephone: 1800 350 622
Fax: +61 2 9737 9414
Email: info@motoractive.com.au


Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to NOHSC Criteria, and ADG Code.

COMBUSTIBLE LIQUID, regulated under AS1940 for Bulk Storage purposes only.

CHEMWATCH HAZARD RATINGS



RISK

Risk Codes
R65
R67

Risk Phrases

- HARMFUL- May cause lung damage if swallowed.
- Vapours may cause drowsiness and dizziness.

SAFETY

Safety Codes
S36
S37
S401

Safety Phrases

- Wear suitable protective clothing.
- Wear suitable gloves.
- To clean the floor and all objects contaminated by this material, use water and detergent.
- Keep away from food, drink and animal feeding stuffs.
- If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).

continued...

MEGUIAR'S G120 - HOT SHINE TIRE DRESSING

Chemwatch Independent Material Safety Data Sheet
Issue Date: 1-Sep-2011
C9317EC

CHEMWATCH 4827-55
Version No:5
CD 2011/2 Page 2 of 6

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
alkanes, C12- 14- iso-	68551-19-9	60-90
polydimethylsiloxane	63148-62-9	15-40

Section 4 - FIRST AID MEASURES

SWALLOWED

- - If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Avoid giving milk or oils.
- Avoid giving alcohol.

EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- - If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

NOTES TO PHYSICIAN

- Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically.
- For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:
- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
 - Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO₂ 50 mm Hg) should be intubated.
 - Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
 - A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- - Water spray or fog.
- Alcohol stable foam.
- Dry chemical powder.
- Carbon dioxide.

FIRE FIGHTING

- - Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.

continued...

MEGUIAR'S G120 - HOT SHINE TIRE DRESSING

Chemwatch Independent Material Safety Data Sheet

Issue Date: 1-Sep-2011

C9317EC

CHEMWATCH 4827-55

Version No:5

CD 2011/2 Page 3 of 6

Section 5 - FIRE FIGHTING MEASURES

- Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area.

FIRE/EXPLOSION HAZARD

- - Combustible.
- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).

Combustion products include:.

carbon dioxide (CO₂).

other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

FIRE INCOMPATIBILITY

- - Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM

None

Personal Protective Equipment

Breathing apparatus.

Chemical splash suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- - Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.

MAJOR SPILLS

- Moderate hazard.
- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- - Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

SUITABLE CONTAINER

- - Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

- - Avoid reaction with oxidising agents.
- Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.

STORAGE REQUIREMENTS

- - Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.

continued...

MEGUIAR'S G120 - HOT SHINE TIRE DRESSING

Chemwatch Independent Material Safety Data Sheet

Issue Date: 1-Sep-2011

C9317EC

CHEMWATCH 4827-55

Version No:5

CD 2011/2 Page 4 of 6

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- alkanes, C12- 14- iso- :
- polydimethylsiloxane:

CAS:68551- 19- 9

CAS:63148- 62- 9

PERSONAL PROTECTION

RESPIRATOR

•Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

EYE

- - Safety glasses with side shields.

- Chemical goggles.

- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

- - Wear chemical protective gloves, eg. PVC.

- Wear safety footwear or safety gumboots, eg. Rubber.

OTHER

- - Overalls.

- P.V.C. apron.

- Barrier cream.

- Skin cleansing cream.

ENGINEERING CONTROLS

- Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Clear liquid with a very slight chemical odour; not miscible with water.

PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

Floats on water.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	45- 55 cps cSt@40°C
Boiling Range (°C)	232	Solubility in water (g/L)	Immiscible
Flash Point (°C)	66 (PMCC)	pH (1% solution)	Not Applicable
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Not Available
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	0.823- 0.857
Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	>1
Volatile Component (%vol)	Nil (VOC)	Evaporation Rate	Not Available

continued...

MEGUIAR'S G120 - HOT SHINE TIRE DRESSING

Chemwatch Independent Material Safety Data Sheet
Issue Date: 1-Sep-2011
C9317EC

CHEMWATCH 4827-55
Version No:5
CD 2011/2 Page 5 of 6

Section 10 - STABILITY AND REACTIVITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- - Presence of incompatible materials.
 - Product is considered stable.
 - Hazardous polymerisation will not occur.
- For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

- HARMFUL- May cause lung damage if swallowed.
- Vapours may cause dizziness or suffocation.
- Vapours may cause drowsiness and dizziness.

CHRONIC HEALTH EFFECTS

- - Generally not applicable.

TOXICITY AND IRRITATION

MEGUIAR'S G120 - HOT SHINE TIRE DRESSING:

- Not available. Refer to individual constituents.

ALKANES, C12-14-ISO-:

- No significant acute toxicological data identified in literature search.

POLYDIMETHYLSILOXANE:

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Inhalation (rat) LC50: >1100 mg/m³*

Oral (rat) LD50: >35000 mg/kg*

Dermal (rabbit) LD50: >3000 mg/kg*

- For siloxanes:

Effects which based on the reviewed literature do not seem to be problematic are acute toxicity, irritant effects, sensitization and genotoxicity.

Some studies indicate that some of the siloxanes may have endocrine disrupting properties, and reproductive effects have caused concern about the possible effects of the siloxanes on humans and the environment.

Only few siloxanes are described in the literature with regard to health effects, and it is therefore not possible to make broad conclusions and comparisons of the toxicity related to short-chained linear and cyclic siloxanes based on the present evaluation.

Data are primarily found on the cyclic siloxanes D4 (octamethylcyclotetrasiloxane) and D5 (decamethylcyclopentasiloxane) and the short-linear HMDS (hexamethyldisiloxane).

The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

No toxic response noted during 90 day subchronic inhalation toxicity studies

The no observable effect level is 450 mg/m³.

Non-irritating and non-sensitising in human patch test. [Xerox]*

IRRITATION

Eye (rabbit): 100 mg/1h - Mild

Section 12 - ECOLOGICAL INFORMATION

No data

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
Meguiar' s G120 - Hot Shine Tire Dressing	No Data Available	No Data Available		
alkanes, C12- 14- iso-	No Data Available	No Data Available		
polydimethylsiloxane	No Data Available	No Data Available	LOW	

continued...

MEGUIAR'S G120 - HOT SHINE TIRE DRESSING

Chemwatch Independent Material Safety Data Sheet
Issue Date: 1-Sep-2011
C9317EC

CHEMWATCH 4827-55
Version No:5
CD 2011/2 Page 6 of 6

Section 13 - DISPOSAL CONSIDERATIONS

- - Containers may still present a chemical hazard/ danger when empty.
 - Return to supplier for reuse/ recycling if possible.
- Otherwise:
- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
 - Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

Section 14 - TRANSPORTATION INFORMATION

Labels Required: COMBUSTIBLE LIQUID, regulated under AS1940 for Bulk Storage purposes only.

HAZCHEM:

None (ADG7)

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: ADG7, UN, IATA, IMDG

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE S5

REGULATIONS

Regulations for ingredients

alkanes, C12-14-iso- (CAS: 68551-19-9) is found on the following regulatory lists;

"Australia Inventory of Chemical Substances (AICS)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Fragrance Association (IFRA) Survey: Transparency List", "OECD Representative List of High Production Volume (HPV) Chemicals"

polydimethylsiloxane (CAS: 63148-62-9) is found on the following regulatory lists;

"Australia Inventory of Chemical Substances (AICS)", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances", "OECD Representative List of High Production Volume (HPV) Chemicals"

No data for Meguiar's G120 - Hot Shine Tire Dressing (CW: 4827-55)

Section 16 - OTHER INFORMATION

- Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

- The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 1-Sep-2011
Print Date: 1-Sep-2011

This is the end of the MSDS.