# **Material Safety Data Sheet**

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

### 1. MATERIAL AND COMPANY IDENTIFICATION

Material Name : Retinax Grease CMX 2

**Uses** : Automotive and industrial grease.

Manufacturer/Supplier : SOPUS Products

PO BOX 4427

Houston, TX 77210-4427

USA

**MSDS Request** : 877-276-7285

**Emergency Telephone Number** 

**Spill Information** : 877-242-7400 **Health Information** : 877-504-9351

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Identity	CAS No.	Concentration	
Molybdenum disulphide	1317-33-5	1.00 - 5.00 %	
Tris[bis(2-	15991-76-1	1.00 - 5.00 %	
ethylhexyl)dithiocarbamato-			
S,S'] antimony			

A lubricating grease consisting of highly-refined mineral oil and additives.

The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.

### 3. HAZARDS IDENTIFICATION

Appearance and Odour	<ul><li>Emergency Overview</li><li>Dark grey. Semi-solid at room temperature. Slight hydrocarbon.</li></ul>
Health Hazards	: High-pressure injection under the skin may cause serious damage including local necrosis.
Safety Hazards Environmental Hazards	<ul><li>Not classified as flammable but will burn.</li><li>Not classified as dangerous for the environment.</li></ul>

**Health Hazards** : Not expected to be a health hazard when used under normal

conditions.

**Health Hazards** 

**Inhalation** : Under normal conditions of use, this is not expected to be a

primary route of exposure.

**Skin Contact** : Prolonged or repeated skin contact without proper cleaning can

clog the pores of the skin resulting in disorders such as oil

acne/folliculitis.

**Eye Contact** : May cause slight irritation to eyes.

**Ingestion** : Low toxicity if swallowed.

Other Information : High-pressure injection under the skin may cause serious

damage including local necrosis. Used grease may contain

# According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# **Material Safety Data Sheet**

harmful impurities.

Signs and Symptoms : Local necrosis is evidenced by delayed onset of pain and tissue

damage a few hours following injection. Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in

nausea, vomiting and/or diarrhoea.

Aggravated Medical

Condition

 Pre-existing medical conditions of the following organ(s) or organ system(s) may be aggravated by exposure to this

material: Skin.

**Environmental Hazards Additional Information** 

Not classified as dangerous for the environment.

Under normal conditions of use or in a foreseeable emergency,

this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

#### 4. FIRST AID MEASURES

General Information : Not expected to be a health hazard when used under normal

conditions.

**Inhalation** : No treatment necessary under normal conditions of use. If

symptoms persist, obtain medical advice.

Skin Contact : Remove contaminated clothing. Flush exposed area with water

and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention. When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop. Obtain medical attention even in the absence of

apparent wounds.

**Eye Contact** : Flush eye with copious quantities of water. If persistent

irritation occurs, obtain medical attention.

Ingestion : In general no treatment is necessary unless large quantities

are swallowed, however, get medical advice.

Advice to Physician : Treat symptomatically. High pressure injection injuries require

prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function. Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign

material should be performed under general anaesthetics, and

wide exploration is essential.

#### 5. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

Flash point : >= 260 °C / 500 °F (Cleveland Open Cup)
Upper / lower : Typical 1 - 10 %(V)(based on mineral oil)

Upper / lower Flammability or

# **Material Safety Data Sheet**

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Explosion limits** 

**Auto ignition temperature** 

**Specific Hazards** 

 $: > 320 \, ^{\circ}\text{C} / 608 \, ^{\circ}\text{F}$ 

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases

(smoke). Carbon monoxide. Unidentified organic and inorganic

compounds.

**Suitable Extinguishing** 

Media

Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

**Unsuitable Extinguishing** 

Media

Do not use water in a jet.

**Protective Equipment for** 

**Firefighters** 

Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.

#### 6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe all relevant local and international regulations.

Protective measures : Avoid contact with skin and eyes. Use appropriate containment

to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or

other appropriate barriers.

Clean Up Methods : Shovel into a suitable clearly marked container for disposal or

reclamation in accordance with local regulations.

#### 7. HANDLING AND STORAGE

General Precautions : Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine

appropriate controls for safe handling, storage and disposal of

this material.

Handling : Avoid prolonged or repeated contact with skin. Avoid inhaling

vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment

should be used.

Storage : Keep container tightly closed and in a cool, well-ventilated

place. Use properly labelled and closeable containers. Storage

Temperature: 0 - 50 °C / 32 - 122 °F

Recommended Materials : For containers or container linings, use mild steel or high

density polyethylene.

Unsuitable Materials : PVC.

**Additional Information** : Polyethylene containers should not be exposed to high

temperatures because of possible risk of distortion.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Occupational Exposure Limits**

# **Material Safety Data Sheet**

Material	Source	Туре	ppm	mg/m3	Notation
Molybdenu	ACGIH	TWA(Respira		0.5 mg/m3	as Mo
m		ble fraction.)			
disulphide	00114 74	DEL		5/0	
Molybdenu	OSHA Z1	PEL		5 mg/m3	as Mo
m disulphide					
Molybdenu	OSHA Z1A	TWA		5 mg/m3	as Mo
m					
disulphide					
Molybdenu m	ACGIH	TWA(Inhalable fraction.)		10 mg/m3	as Mo
disulphide					
Molybdenu	ACGIH	TWA(Respira		3 mg/m3	as Mo
m		ble fraction.)			
disulphide	00114 74	DEL /E . I		1.5 / 0	
Molybdenu	OSHA Z1	PEL(Total		15 mg/m3	as Mo
m		dust.)			
disulphide	00114 74 4	T\A/A/T - ( - 1		40/0	84-
Molybdenu	OSHA Z1A	TWA(Total dust.)		10 mg/m3	as Mo
m disulphide		dusi.)			
Tris[bis(2-	ACGIH	TWA		0.5 mg/m3	as Sb
ethylhexyl)	ACCIII	1 4 4 7		0.5 mg/m5	as ob
dithiocarba					
mato-S,S']					
antimony					
Tris[bis(2-	OSHA Z1	PEL		0.5 mg/m3	as Sb
ethylhexyl)					
dithiocarba					
mato-S,S']					
antimony					
Tris[bis(2-	OSHA Z1A	TWA		0.5 mg/m3	as Sb
ethylhexyl)					
dithiocarba					
mato-S,S']					
antimony	100111	T) A / A / B A' = ( )		5/0	
Oil mist,	ACGIH	TWA(Mist.)		5 mg/m3	
mineral	ACCILL	OTEL (NA:-+)		10 0	
Oil mist,	ACGIH	STEL(Mist.)		10 mg/m3	
mineral					

Additional Information : Due to the product's semi-solid consistency, generation of

mists and dusts is unlikely to occur.

**Exposure Controls** : The level of protection and types of controls necessary will vary

depending upon potential exposure conditions. Select controls

based on a risk assessment of local circumstances.

Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or

1910.1200

# **Material Safety Data Sheet**

mist formed, there is greater potential for airborne

concentrations to be generated.

**Personal Protective** 

Equipment

**Respiratory Protection** 

Personal protective equipment (PPE) should meet

recommended national standards. Check with PPE suppliers. No respiratory protection is ordinarily required under normal

conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point

>65 °C (149 °F)].

**Hand Protection** : Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye Protection : Wear safety glasses or full face shield if splashes are likely to

occur.

Protective Clothing : Skin protection not ordinarily required beyond standard issue

work clothes.

Monitoring Methods : Monitoring of the concentration of substances in the breathing

zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also

be appropriate.

**Environmental Exposure** 

**Controls** 

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local

environmental legislation.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Dark grey. Semi-solid at room temperature.

Odour : Slight hydrocarbon.
pH : Not applicable.
Initial Boiling Point and : Data not available

Boiling Range

Dropping point : Typical 220 °C / 428 °F

Flash point :  $>= 260 \, ^{\circ}\text{C} \, / \, 500 \, ^{\circ}\text{F}$  (Cleveland Open Cup) Upper / lower Flammability : Typical 1 - 10 %(V) (based on mineral oil)

or Explosion limits

### According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

# **Material Safety Data Sheet**

 $: > 320 \, ^{\circ}\text{C} / 608 \, ^{\circ}\text{F}$ Auto-ignition temperature

Vapour pressure < 0.5 Pa at 20 °C / 68 °F (estimated value(s))

Specific gravity : Typical 0.955 : Typical 911 g/cm3 Density

Water solubility : Negligible.

n-octanol/water partition coefficient (log Pow)

: > 6 (based on information on similar products)

Vapour density (air=1) : > 1 (estimated value(s)) Evaporation rate (nBuAc=1) : Data not available

#### 10. STABILITY AND REACTIVITY

**Stability** : Stable.

**Conditions to Avoid** Extremes of temperature and direct sunlight.

Materials to Avoid Strong oxidising agents.

**Hazardous Decomposition** 

Hazardous decomposition products are not expected to form **Products** 

during normal storage.

#### 11. TOXICOLOGICAL INFORMATION

**Basis for Assessment** Information given is based on data on the components and the

toxicology of similar products.

Expected to be of low toxicity: LD50 > 5000 mg/kg, Rat **Acute Oral Toxicity Acute Dermal Toxicity** Expected to be of low toxicity: LD50 > 5000 mg/kg, Rabbit **Acute Inhalation Toxicity** Not considered to be an inhalation hazard under normal

conditions of use.

**Skin Irritation** Expected to be slightly irritating. Prolonged or repeated skin

contact without proper cleaning can clog the pores of the skin

resulting in disorders such as oil acne/folliculitis.

**Eye Irritation** Expected to be slightly irritating.

**Respiratory Irritation** Inhalation of vapours or mists may cause irritation.

Sensitisation Not expected to be a skin sensitiser.

**Repeated Dose Toxicity** Not expected to be a hazard.

Mutagenicity Not considered a mutagenic hazard.

Product contains mineral oils of types shown to be non-Carcinogenicity

carcinogenic in animal skin-painting studies. Highly refined

mineral oils are not classified as carcinogenic by the

International Agency for Research on Cancer (IARC). Other components are not known to be associated with carcinogenic

effects.

Material	:	Carcinogenicity Classification
Molybdenum disulphide	:	ACGIH Group A3: Confirmed animal carcinogen with unknown
		relevance to humans.

Reproductive and **Developmental Toxicity Additional Information** 

: Not expected to be a hazard.

Used grease may contain harmful impurities that have accumulated during use. The concentration of such harmful impurities will depend on use and they may present risks to health and the environment on disposal. ALL used grease should be handled with caution and skin contact avoided as far

MSDS\_US Print Date 04/30/2011

1910.1200

# **Material Safety Data Sheet**

as possible. High pressure injection of product into the skin

may lead to local necrosis if the product is not surgically removed.

#### 12. ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.

: Poorly soluble mixture. May cause physical fouling of aquatic **Acute Toxicity** 

> organisms. Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l (to aquatic organisms) (LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract). Mineral oil is not expected to cause any chronic effects to aquatic organisms at concentrations less than 1 mg/l.

**Mobility** Semi-solid under most environmental conditions. Floats on

water. If it enters soil, it will adsorb to soil particles and will not

be mobile.

Persistence/degradability Expected to be not readily biodegradable. Major constituents

> are expected to be inherently biodegradable, but the product contains components that may persist in the environment. Contains components with the potential to bioaccumulate.

Bioaccumulation **Other Adverse Effects** 

Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not

expected to have ozone depletion potential, photochemical

ozone creation potential or global warming potential.

# 13. DISPOSAL CONSIDERATIONS

**Material Disposal** Recover or recycle if possible. It is the responsibility of the

waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in

drains or in water courses.

**Container Disposal** Dispose in accordance with prevailing regulations, preferably

> to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

Disposal should be in accordance with applicable regional, **Local Legislation** 

national, and local laws and regulations.

#### 14. TRANSPORT INFORMATION

### **US Department of Transportation Classification (49CFR)**

This material is not subject to DOT regulations under 49 CFR Parts 171-180.

#### **IMDG**

This material is not classified as dangerous under IMDG regulations.

Retinax Grease CMX 2

MSDS# 400918E

Version 3.0

Effective Date 07/07/2008

According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

# **Material Safety Data Sheet**

### IATA (Country variations may apply)

This material is not classified as dangerous under IATA regulations.

#### 15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

# **Federal Regulatory Status**

#### **Notification Status**

DSL All components listed.
EINECS All components listed.
TSCA All components listed.

# Comprehensive Environmental Release, Compensation & Liability Act (CERCLA)

Retinax Grease CMX 2 () Reportable quantity: 40 lbs

Tris[bis(2ethylhexyl)dithiocarbamato-S,S'] antimony (15991-76-1)

#### SARA Hazard Categories (311/312)

No SARA 311/312 Hazards.

### SARA Toxic Release Inventory (TRI) (313)

Tris[bis(2- 2.50% ethylhexyl)dithiocarbamato-S,S'] antimony (15991-76-1)

#### **State Regulatory Status**

### California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

This material does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

### **New Jersey Right-To-Know Chemical List**

Molybdenum disulphide (1317-33-5)

Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony
(15991-76-1)

Listed.
Listed.

Retinax Grease CMX 2

MSDS# 400918E

Version 3.0

Effective Date 07/07/2008

According to OSHA Hazard Communication Standard, 29 CFR

1910.1200

# **Material Safety Data Sheet**

### **16. OTHER INFORMATION**

NFPA Rating (Health,

: 0, 1, 0

Fire, Reactivity)

MSDS Version Number : 3.0

MSDS Effective Date : 07/07/2008

MSDS Revisions : A vertical bar (|) in the left margin indicates an amendment

from the previous version.

MSDS Regulation : The content and format of this MSDS is in accordance with the

OSHA Hazard Communication Standard, 29 CFR 1910.1200.

MSDS Distribution : The information in this document should be made available to

all who may handle the product.

Disclaimer : The information contained herein is based on our current

knowledge of the underlying data and is intended to describe the product for the purpose of health, safety and environmental requirements only. No warranty or guarantee is expressed or implied regarding the accuracy of these data or the results to

be obtained from the use of the product.